



GENERAL DESCRIPTION

Junckers Rustic TopOil is used for refreshing and regular maintenance of indoor wooden floors pre-treated with one of Junckers Rustic oils.

The oil is quick drying and ready for light traffic after 30-60 minutes.

Use Junckers TopOil only when the existing oiled surface is sound and stable.

PRODUCT DESCRIPTION

Product: Waterbased air-drying alkyd oil.

Package sizes: 1 litre, 2.5 litre and 10 litre.

Appearance: Dries to colourless ultra matt appearance.

TECHNICAL DATA

Coverage: 30-50 m² per litre.

Before application: Shake well before use.

Application tools: Flat floor mop or cotton cloth.

Surface temperature: Minimum 15° C.

Dilution: Delivered ready for use. Dilution is not recommended.

Drying time:

Ready for light traffic after 30-60 minutes at 20° C and 50 % RH.

Fully cured after 24 hours.

Cleaning of tools: Soap and water immediately after use.

Storage: Lasts for 2 years if unopened and stored at 20° C. Not to be exposed to temperatures below 0° C.

SYSTEM RECOMMENDATIONS

All areas:

1 x Junckers Rustic TopOil
+ 30-60 minutes drying time

The frequency of treatment varies with the amount of traffic on the floor. The more traffic the higher the frequency of the treatment.

DIRECTION FOR USE

Maintenance of sound and stable oiled floors:

The oiled surface must be absolutely clean, dry and free from dust, grease, polish and detergent residue. Dirt and irregularities can be removed by e.g. Junckers Neutralizer, sanding with fine-grained sandpaper, 180-240 grit, or a polishing machine equipped with a corresponding pad. Remove sanding dust with a vacuum cleaner.

It is important to ensure that the priming oil is intact and is one of Junckers oils before applying Junckers Rustic TopOil. If the floor has not been treated with one of Junckers oils, it is necessary to sand the floor and treat with Junckers Rustic Oil or Junckers Rustic Solid 100 Oil, before use of Junckers Rustic TopOil.

Apply an even thin layer. Please note that the oil hardens quickly so care should be taken to spread and work the oil before it dries. Keep any overlaps with dry areas to a minimum. If there are blotches after application, polish these when dry with a green scrubbing sponge or on more extensive areas with a green pad, or a polishing machine with a polishing disc.

Floors regularly maintained with Junckers Rustic TopOil can be spot repaired in walking lanes and other areas with high traffic.

Surfaces worn through:

If the surface is not sound and stable the floor must first be sanded followed by application of Junckers Rustic Oil or Junckers Rustic Solid 100 Oil.

IMPORTANT

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

FURTHER INFORMATION

Products:

F 2.1 - Junckers Rustic Oil
F 2.4 - Junckers Rustic Solid 100 Oil
F 10.3 - Junckers SylvaNeutralizer