

MYRIAD Tiles



Caractéristiques	Technische Daten	Technical details	
Mode de fabrication	Herstellungsort	Manufacturing method	Tufted
Aspect	Art des Flors	Pile type	Looppile
Type de teinture	Art der Färbung	Dyeing method	Solution Dyed
Surface	Polmaterial	Pile content	100% ECONYL® recycled Polyamide (Nylon)
Jauge	Teilung	Gauge	1/10
Dossier	Rücken	Backing	Bitumen with glasfiberscrim
Poids du velours	Poleinsatzgewicht	Pile weight	ca. 680 gr/m ²
Hauteur du velours	Polhöhe	Pile height	ca. 5,0 mm
Epaisseur totale	Gesamtdicke	Total thickness	ca. 8,0 mm
Poids total	Gesamtgewicht	Total weight	ca. 4450 gr/m ²
Nombre de points	Polnoppenzahl	Tuft density	ca. 180 000/m ²
Dimension	Dimension	Dimension	50 x 50 cm
Classement feu	Brennverhalten	Flammability classification	Bfl S1 according to EN13501-1
Classement antistatique	Antistatisches Verhalten	Electrostatic properties	Walking Test < 2,0 KV Resistance ≥ 10 ¹⁰
Domaine d'usage	Einsatzbereich	Suitability	EN1307 - 33 - Heavy Commercial
Isolation phonique	Trittschalldämmung	Sound absorption	ΔLw - 28 dB ISO 140-8
Solidité des coloris :	Farbechtheit :	Colour fastness :	
Lumière	Lichtechtheit	To light	≥ 7 according to ISO 105-B02
Frottement	Reibechtheit	To rubbing	≥ 4 according to ISO 105-X12
Resistance au chlor	Chlorechtheit	Bleach resistance	Yes

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.


This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "watermarking". The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.



We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.



15

Manufactured by :
TAPIBEL NV.
Industrielaan 4
B-3900 Overpelt

DOP 000553T-001
EN 14041





EN 1307

MYRIAD Tiles

For use as floor covering in buildings (EN 14041) according to the manufacturer's specifications



LEED  - requirements fulfilled