

QUALITY DATE: 14/07/2014
ORDER CODE REPLACES: 9/05/2012

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
ANTISOIL
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

WOOLTOUCH SB/DL
WLT

± 400 & 500
COLLECTION
1/10" SAXONY

PIECE DYED

WO
WOOLMARK
HEAVY DUTY CONTRACT - STAIRS

✓

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.890
± 3.080

± 9,0
± 11,0
± 212.760
± 39,40
± 54,00

±
±

± 25
PILE IN

✓

✓

✓

✓

✓

✓

✓

EF3AB5EO

23447

CL. 33
Commercial Heavy



LC5




Bfl-s1




LOW RADIUS

QUALITY



DIMENSIONAL STABILITY			EN 986	≤
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	±
SOUND ABSORPTION	(±)	α _s	ISO 354 - 125 Hz	±
	(±)		250Hz	±
	(±)		500Hz	±
	(±)		1000Hz	±
	(±)		2000Hz	±
(±)	4000Hz	±		
SOUND ABSORPTION	(±)	α _w	EN ISO 11654	±
THERMAL RETENTION	(±) m ² /KW		ISO 8302	± 0,177 
TOG rating	(±)			± 1,77
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	<
SURFACE RESISTANCE R _{oT}	(±) ohm		ISO 10965	≤
SURFACE RESISTANCE R _{dT}	(±) ohm		ISO 10965	≤
LIGHTFASTNESS			ISO 105-B02	≥ 5
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 4-5
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3-4
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 4-5
WATERFASTNESS STAINING			ISO 105-E01	≥ 3-4

LABEL CE



DOP-CPR-1038-113602

EN 14041

EN 1307

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE
FROM

<u>SB/DL 400</u>	WLT	<u>SB/DL 500</u>
212	TOBACCO 2	212
220	ACORN	220
230	FLAX	230
250	MAGNOLIA	250
254	SHELL	254
275	ALMOND 5	275
289	HAVANNA 9	289
295	SEPIA 5	295
422	CORNSTALK 2	422
432	BAMBOO MAT 2	432
442	IVORY 2	442
482	BARLEY 2	482
805	EBONY 5	805
830	ASH	830
850	MOONBEAM	850
870	SILVER	870

AVAILABLE
FROM

<u>SB/DL 400</u>	WLT	<u>SB/DL 500</u>

