

QUALITY DATE: 9/05/2014  
ORDER CODE REPLACES: 24/02/2011

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
ANTISOIL  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (± 15%) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM ✓  
LIVING ROOM ✓  
OFFICE ✓  
CASTOR ROLLCHAIRS DOMESTIC USE ✓  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE ✓  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING ✓  
BATH ROOM ✓  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION  
CLASSIFICATION BS7131

EN 13501-1

BS 4790

**SMARAGD KT SMK**  
**SMK**

± 400 & 500  
COLLECTION  
5/64" CUT PILE

PIECE DYED

PA



WOVEN

TEXTILE BACKING C-BACK

± 900  
± 2.060

± 5,0  
± 7,5  
± 307.440  
± 50,40  
± 61,00

±

±

±



AF338946

23451  
Z-156.601-952 - PA 6.6 / 121

CL. 23 - CL. 32  
Domestic Heavy - Commercial General



LC3



Cfl-s1



