

Bounty

Tuft gauge	5/64 cut pile		ISO 2424
Pilecomposition	100% PES		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	Duo Backing		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1650 gr/m ²		ISO 8543
Total weight	Duo Backing : 2500 gr/m ²	± 15%	ISO 8543
Pile height	11 mm	± 2 mm	ISO 1766
Total Height	Duo Backing : 13 mm		ISO 1765
Number of knots	277.750/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1		EN 13501-1
Use Area	Heavy domestic use (23)		EN 1307
GUT Nr.	AB099C55 GUT		www.pro-dis.info
Thermal resistance	0,135 M ² KW		ISO 8302
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Comments	Micropes		

Floorsymbols



Certificates



2019

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-025AB349

Reaction to fire:
Cfl-s1
1658

Slip resistance: DS

Resilient floor
covering to be
used within a
building



Intenza
the ultimate in soft carpets

