

Kasbar new UX

provisionnally

| | | | |
|---|--|--|--|
| 1/10" scroll | 1/10" scroll | 1/10" scroll | 1/10" scroll |
| 100% polyamide | 100% polyamide | 100% Polyamide | 100% polyamide |
| RUG Ultratex® | DOSSIER Ultratex® | RÜCKEN Ultratex® | BACKING Ultratex® |
| POOLHOOGTE ± 9 mm | HAUTEUR DU VELOURS ± 9 mm | POLHÖHE ± 9 mm | PILE HEIGHT ± 9 mm |
| TOTALE HOOGTE ± 12 mm | HAUTEUR TOTALE ± 12 mm | GESAMTHÖHE ± 12 mm | TOTAL HEIGHT ± 12 mm |
| POOLGEWICHT ± 450 g/m ² | POIDS DU VELOURS ± 450 g/m ² | POLGEWICHT ± 450 g/m ² | PILE WEIGHT ± 450 g/m ² |
| TOTAAL GEWICHT ± 1.200 g/m ² | POIDS TOTAL ± 1.200 g/m ² | GESAMTGEWICHT ± 1.200 g/m ² | TOTAL WEIGHT ± 1.200 g/m ² |
| AANTAL NOPPEN/M ² ± 180 000 | NOMBRE DE POINTS/M ² ± 180 000 | NOPPEN/M ² ± 180 000 | TUFT DENSITY/M ² ± 180 000 |
| AANBEVOLEN LEGWIJZE • Universele fixeerlijm • Verhuislijm | POSE PRÉCONISÉE • Produit de maintien • Fixateur | EMPFOHLENE VERLEGEART • Universalfixierung • Wiederaufnahmeklebstoff | INSTALLATION METHOD • Release bond |
| LICHTECHTHEID ≥ 5-6 | RÉSISTANCE À LA LUMIÈRE ≥ 5-6 | LICHTECHTHEIT ≥ 5-6 | LIGHT FASTNESS ≥ 5-6 |
| WATERECHTHEID ≥ 4-5 | RÉSISTANCE À LA LUMIÈRE ≥ 4-5 | WASSERECHTHEIT ≥ 4-5 | WATER RESISTANCE ≥ 4-5 |
| BRANDKLASSE Efl (EN 13501-1) | CLASSEMENT FEU Efl (EN 13501-1) | BRANDKLASSE Efl (EN 13501-1) | FIRE CLASS Efl (EN 13501-1) |



Onder voorbehoud van wijzingen van de technische specificaties - Sous réserve de modifications techniques - Unter Vorbehalt von technischen Änderungen - All rights reserved to alter technical specification

| | | | | | | | |
|--------|----|----|----|----|----|----|----|
| Kasbar | 33 | 35 | 43 | 65 | 78 | 95 | 97 |
| ca 4m | • | • | • | • | • | • | • |



Kasbar new UX




33




35



43



65



78



95



97